

# SDB PRODUCT SPECIFICATIONS



	Cable		Handle		Overall		Carrying Case
	Length	Diameter	Length	Width	Length	Weight	Weight
<b>DV-100</b>	18" 457.2mm	.4" 10.5mm	6" 152.4mm	11.43" 290.3mm	24" 609.6mm	8 oz. 227g	1lb. 8.3 oz. 689g
<b>DV-618</b>	18" 457.2mm	.23" 5.8mm	6" 152.4mm	11.43" 290.3mm	24" 609.6mm	5.4 oz. 153g	1lb. 5.7 oz. 615g
<b>DV-300</b>	36" 914.4mm	.4" 10.5mm	6" 152.4mm	11.43" 290.3mm	42" 1066.8mm	10 oz. 284g	2lb. 9.7 oz. 1082g
<b>DV-636</b>	36" 914.4mm	.23" 5.8mm	6" 152.4mm	11.43" 290.3mm	42" 1066.8mm	5.8 oz. 165g	2lb. 5.5 oz. 1063g
<b>DV-480</b>	48" 1219.2mm	.4" 10.5mm	6" 152.4mm	11.43" 290.3mm	54" 1371.6mm	11.5 oz. 318g	5lb. 2268g
<b>DV-720</b>	72" 1828.8mm	.4" 10.5mm	6" 152.4mm	11.43" 290.3mm	78" 1981.2mm	16 oz. 454g	5lb. 4.5 oz. 2395g
<b>DV-960</b>	96" 2438.4mm	.4" 10.5mm	6" 152.4mm	11.43" 290.3mm	102" 2590.8mm	18 oz. 510g	5lb. 6.5 oz. 2452g
<b>Field of View:</b>	40°						
<b>Optimal Viewing Distance - Min.</b>	.8"/20mm						
<b>Optimal Viewing Distance - Max.</b>	Dependent upon ambient lighting conditions						
<b>Lamp Volts</b>	2.7v						
<b>Power Source</b>	2 AA batteries (not included)						
<b>Pressure Necessary to Operate Lamp</b>	2.9 avg. p/psi 3.2 max. p/psi						

\*DV-618 and DV-636 models have .23" diameter, flexible, non-obedient cable.  
All other models have .4" diameter, flexible, obedient cable.